



Full HD Resolution

1080P high-resolution with real-time frame rate, ensuring that you capture all the details you need

Viewing Window and ePTZ

Customize your Region of Interest (ROI) by simply drawing a rectangle on the full view. Being able to digitally move the ROI is an advantage for a fixed camera since it can utilize the virtual auto pan along with preset point settings to display vivid details from the HD video.

Features

- 1/2.7" 2 megapixel CMOS sensor
- Real-time H.264/MPEG-4/MJPEG
- Max. resolution 1920x1080 at 30 fps
- Four simultaneous streams
- ePTZ for virtual PTZ operation
- Built-in 2.8~12 mm, F1.2 fixed lens
- IR-Cut Removable filter for day/night use
- 2-way audio support (half-duplex)
- SD/SDHC card slot for camera-side storage
- Tamper detection
- Motion detection
- Privacy mask
- Advanced event management
- Advanced web user interface
- HTML code example of streaming
- Supports IPv6, 802.1x, QoS, CoS, and SNMPv1/v2/v3
- Multicast video/audio stream
- HTTPS secured streaming
- 3GPP mobile surveillance
- Samba client for NAS
- Multiple access lists
- Windows Vista LLTD
- Power over Ethernet (PoE)
- TV output support
- DI/DO support for external devices
- RS-485 for external PTZ connection
- Unified D-Link SDK
- ONVIF compliant

Full HD Day & Night Network Camera



The DCS-3715 is a full HD, full frame rate network camera with H.264 compression that delivering vivid high-quality live video over the Internet. The high-quality video feed is convenient for searching and identifying any necessary details such as a security breach. The DCS-3715 features multiple streaming feeds and flexible viewing window settings for multi-purpose surveillance (regular recording or mobile view). An IR-cut removable (ICR) filter is equipped for day and night views. There is also a built-in SD card slot that the camera can use for local backup to store important events on an easily retrievable SD card.

Full HD Surveillance

The DCS-3715 delivers high quality streaming Full HD 16:9 widescreen IP video surveillance. The high-performance vari-focal lens makes the DCS-3715 suitable for a variety of environments and provides a high-quality image. In order to take advantage of the high resolution, the "viewing window" is designed to provide the user with a flexible setting to monitor multiple ROIs (Region of Interest) with a single camera. The "ePTZ" functions to simulate wide area surveillance by using digital zoom along with pan/tilt control.

Multiple Video Streams

The DCS-3715 supports simultaneous streaming of H.264, MPEG-4, and MJPEG video to provide both high-quality and bandwidth-efficient compression formats. H.264 produces a small file size, making it useful for extended recording with high detail or for use in low-bandwidth networks. MJPEG delivers excellent file integrity, ideal for situations which require extensive image detail. Additionally, the DCS-3715 supports multicast H.264 streaming, allowing users to view the camera feed by subscribing to a multicast IP address on the network.

Flexible Connectivity

The DCS-3715 includes input and output ports for connectivity to external devices such as IR sensors, switches, and alarm relays. It also comes with an RS-485 interface, providing connectivity to an optional pan/tilt scanner. The DCS-3715 also incorporates Power over Ethernet (PoE), allowing it to be easily installed in a variety of locations without the need for supplemental power cabling or a nearby power outlet.

Advanced Web User Interface

The DCS-3715 features D-Link's latest-generation graphical user interface. This freshly-designed web interface features a clean, compact, and professional home screen which dramatically increases usability. Menu navigation is simplified thanks to a tree view which logically groups functions, helping users to quickly find what they need. Likewise, intuitive graphic icons reduce the amount text and clutter within the browser window. New users will appreciate the convenient contextual help which offers an easy way to find assistance with camera management tasks.

D-ViewCam for Management

The included D-Link D-ViewCam™ is sophisticated software which allows users to manage up to 32 network cameras, set e-mail alert notifications, create recording schedules, and use motion detection to automatically record video when movement is detected. D-ViewCam™ also allows users to upload a floor plan to create a realistic layout of the premises where cameras are located, further simplifying the management process.

3GPP Mobile Surveillance

Support for 3GPP Mobile Surveillance allows users to view a live video feed from a 3GPP compatible mobile device connected to the Internet. This allows users to check the camera's video feed while on the go without a computer.





Full HD Day & Night Network Camera

Technical Specifications

Camera	Hardware Profile	<ul style="list-style-type: none"> 1/2.7" 2 megapixel CMOS sensor 2.8 to 12 mm fixed lens, F1.2 Built-in Infrared-Cut Removable (ICR) Filter module 	<ul style="list-style-type: none"> 29.1° to 118.3° degree horizontal , 16.5° to 63.6° degree vertical viewing angle 256 Mbytes SDRAM 128 Mbytes of flash memory 	
	Image Features	<ul style="list-style-type: none"> Configurable image size, quality, frame rate, and bit rate Time stamp and text overlays 3 configurable motion detection windows Min Illumination: 0.06 lux / F1.2 (Color), 0.001 lux / F1.2 (B/W) 	<ul style="list-style-type: none"> 5 configurable privacy masks Flip & mirror Configurable white balance, shutter speed, brightness, saturation, contrast, sharpness 	
	Video Compression	<ul style="list-style-type: none"> H.264/MPEG4/MJPEG format compression simultaneously JPEG for still image 	<ul style="list-style-type: none"> H.264/MPEG-4 multicast streaming 	
	Video Resolution	1920x1080 @ 30fps, 1280x800 @ 30 fps, 1280x720 @ 30 fps, 640x480 @ 30 fps, 320x240 @ 30 fps, 176x144 @ 30 fps		
	Audio Features	<ul style="list-style-type: none"> GSM-AMR speech encoding, bit rate: 4.75 kbps to 12.2 kbps. MPEG-4 AAC audio encoding, bit rate: 16 kbps to 128 kbps Supports two-way audio and audio mute 		
	Network	Network Protocols	IPv4, IPv6, TCP/IP, UDP, ICMP, DHCP Client, NTP Client (D-Link), DNS Client, DDNS Client (D-Link), SMTP Client, FTP Client, HTTP / HTTPS, Samba Client, PPPoE, UPnP Port Forwarding, RTP / RTSP/ RTCP, IP filtering, 3GPP, LLTD, CoS/QoS, SNMP, IGMP, 802.1x, ONVIF Compliant	
Security		<ul style="list-style-type: none"> Administrator and user group protection Password authentication HTTP and RTSP digest encryption 	<ul style="list-style-type: none"> HTTPS streaming Remote client access control 	
System Integration	System Requirements	<ul style="list-style-type: none"> Operating system: Microsoft Windows 7, Vista, XP, 2000 Browser: Internet Explorer, Firefox 		
	D-ViewCam™ System Requirements	<ul style="list-style-type: none"> Operating System: Microsoft Windows 7 / Vista / XP Web Browser: Internet Explorer 6 or higher 	<ul style="list-style-type: none"> Protocol: Standard TCP/IP 	
	Event Management	<ul style="list-style-type: none"> Motion detection Event notification and upload snapshots/video clips via HTTP, SMTP or FTP Supports multiple HTTP, SMTP and FTP servers 	<ul style="list-style-type: none"> Multiple event notification Multiple recording methods for easy backup 	
	Remote Management	<ul style="list-style-type: none"> Configuration accessible via web browser Take snapshots/video clips and save to local hard drive or NAS via web browser 		
	Surveillance Software Function	<ul style="list-style-type: none"> Remote management/control of up to 32 cameras Viewing of up to 32 cameras on one screen 	<ul style="list-style-type: none"> Supports all management functions provided in web interface Scheduled motion triggered, or manual recording options 	
	Supported PDA, Mobile Phones, and Software	Handsets with 3GPP player, QuickTime 6.5, Real Player 10.5, Windows 2000, XP, Vista, 7 or above		
	External Device Interfaces	<ul style="list-style-type: none"> DI/DO for external sensor and alarm External audio input (MIC in) External Audio/Video output (AV out) TV system switch (NTSC / PAL) 	<ul style="list-style-type: none"> RS485 for pan/tilt scanner SD card slot (with cover) Microphone mute switch 	
General	Power Input	12 V DC 1.25 A, 24 V AC, 50/60 Hz, 802.3af PoE		
	Max. Power Consumption	3.744 watts		
	Operating Temperature	0 to 40 °C (32 to 104 °F)		
	Storage Temperature	-20 to 70 °C (-4 to 158 °F)		
	Humidity	90% non-condensing		
	Weight	605 g (1.62 lbs)		
	Certifications	CE (Class A), CE LVD (EN60965-1), FCC (Class A), ICES-003, C-Tick		
Dimensions				



D-Link Corporation
 No. 289 Xinhui 3rd Road, Neihu, Taipei 114, Taiwan
 Specifications are subject to change without notice.
 D-Link is a registered trademark of D-Link Corporation and its overseas subsidiaries.
 All other trademarks belong to their respective owners.
 ©2011 D-Link Corporation. All rights reserved.
 Release 02 (June 2011)